


Version 2018
CR-DT 电工丝堵



产品特点

- 适用于设备中有备用孔或不用孔的密封
- 材质可选不锈钢、碳钢或黄铜镀镍
- 密封件可选丁腈橡胶或硅胶
- 防止设备内进水并防灰防尘
- 可用于爆炸性环境IIA IIB IIC

符合标准



应用行业



适用环境



防爆标记



防护等级



产品认证



可选附件



防水非防爆型-DTa

公制 订货编号	螺纹接口 AG	主体厚度 H mm	螺纹长度 L mm	对边*对角 SW*E
CR-DTa-M12	M12*1.5	3	5	14*15.5
CR-DTa-M16	M16*1.5	3	6	18*20
CR-DTa-M20	M20*1.5	3	6.5	22*24.4
CR-DTa-M25	M25*1.5	3.5	6.5	28*31.2
CR-DTa-M30	M30*1.5	3.5	7	33*36
CR-DTa-M32	M32*1.5	3.5	7	35*38.5
CR-DTa-M40	M40*1.5	4	8	43*47.3
CR-DTa-M50	M50*1.5	4	8	52*56

德制 订货编号	螺纹接口 AG	主体厚度 H mm	螺纹长度 L mm	对边*对角 SW*E
CR-DTa-PG7	PG7	3	5	14*16
CR-DTa-PG9	PG9	3	6	17*19.5
CR-DTa-PG11	PG11	3	6	20*22.5
CR-DTa-PG13.5	PG13.5	3	6.5	22*24.4
CR-DTa-PG16	PG16	3.5	6.5	24*26.7
CR-DTa-PG21	PG21	3.5	7	30*34
CR-DTa-PG29	PG29	3.5	8	40*43.5
CR-DTa-PG36	PG36	4	9	50*57

美制 订货编号	螺纹接口 AG	主体厚度 H mm	螺纹长度 L mm	对边 SW
CR-DTa-NPT1/4	1/4"	3	5	16
CR-DTa-NPT3/8	3/8"	3	6	20
CR-DTa-NPT1/2	1/2"	3	6.5	24
CR-DTa-NPT3/4	3/4"	3.5	6.5	28
CR-DTa-NPT1	1"	3.5	7	35
CR-DTa-NPT1 1/4	1-1/4"	4	8	45

英制 订货编号	螺纹接口 AG	主体厚度 H mm	螺纹长度 L mm	对边 SW
CR-DTa-G1/4	1/4"	3	5	16
CR-DTa-G3/8	3/8"	3	6	20
CR-DTa-G1/2	1/2"	3	6.5	24
CR-DTa-G3/4	3/4"	3.5	6.5	28
CR-DTa-G1	1"	3.5	7	35
CR-DTa-G1 1/4	1-1/4"	4	8	45

防水防爆型-DTEX

订货编号 公制M	螺纹接口 AG	主体厚度 H mm	螺纹长度 L mm	扳手径 SW
CR-DTEX-M12	M12*1.5	3	8	14
CR-DTEX-M16	M16*1.5	3	8	18
CR-DTEX-M18	M18*1.5	3	8	20
CR-DTEX-M20	M20*1.5	4	9	22
CR-DTEX-M25	M25*1.5	4	9	27
CR-DTEX-M30	M30*2.0	4	10	32
CR-DTEX-M32	M32*1.5	4	10	34
CR-DTEX-M40	M40*1.5	4	12	42
CR-DTEX-M50	M50*1.5	5	13	52
CR-DTEX-M63	M63*1.5	5	14	68

订货编号 德制PG	螺纹接口 AG	主体厚度 H mm	螺纹长度 L mm	扳手径 SW
CR-DTEX-PG7	PG7	3	8	14
CR-DTEX-PG9	PG9	3	8	18
CR-DTEX-PG11	PG11	3	8	20
CR-DTEX-PG13.5	PG13.5	3	8	22
CR-DTEX-PG16	PG16	4	9	24
CR-DTEX-PG21	PG21	4	9	30
CR-DTEX-PG29	PG29	4	10	40
CR-DTEX-PG36	PG36	5	12	50
CR-DTEX-PG42	PG42	5	12	57
CR-DTEX-PG48	PG48	5	12	62

订货编号 美制NPT	螺纹接口 AG	主体厚度 H mm	螺纹长度 L mm	扳手径 SW
CR-DTEX-NPT3/8	3/8"	3	10	20
CR-DTEX-NPT1/2	1/2"	4	10	24
CR-DTEX-NPT3/4	3/4"	4	10	30
CR-DTEX-NPT1	1"	4	12	36
CR-DTEX-NPT1 1/4	1-1/4"	4	12	45
CR-DTEX-NPT1 1/2	1-1/2"	5	12	52
CR-DTEX-NPT2	2"	6	15	65
CR-DTEX-NPT2 1/2	2-1/2"	6	15	80
CR-DTEX-NPT3	3"	7	16	95
CR-DTEX-NPT4	4"	7	16	120

订货编号 英制G	螺纹接口 AG	主体厚度 H mm	螺纹长度 L mm	扳手径 SW
CR-DTEX-G3/8	3/8"	3	10	20
CR-DTEX-G1/2	1/2"	4	10	24
CR-DTEX-G3/4	3/4"	4	10	30
CR-DTEX-G1	1"	4	12	36
CR-DTEX-G1 1/4	1-1/4"	4	12	45
CR-DTEX-G1 1/2	1-1/2"	5	12	52
CR-DTEX-G2	2"	6	15	65
CR-DTEX-G2 1/2	2-1/2"	6	15	80
CR-DTEX-G3	3"	7	16	95
CR-DTEX-G4	4"	7	16	120

圆形防水防爆型-DTb

公制AG 订货编号	主体外径 D mm	螺纹长度 L mm	德制AG 订货编号	主体外径 D mm	螺纹长度 L mm	美制AG 订货编号	英制AG 订货编号	主体外径 D mm	螺纹长度 L mm
CR-DTb-M12	14	5	CR-DTb-PG7	15	5	CR-DTb-G1/4	CR-DTb-NPT1/4	16	5
CR-DTb-M16	18	5	CR-DTb-PG9	20	5	CR-DTb-G3/8	CR-DTb-NPT3/8	20	5
CR-DTb-M20	22	6	CR-DTb-PG11	22	5	CR-DTb-G1/2	CR-DTb-NPT1/2	24	6
CR-DTb-M25	28	7	CR-DTb-PG13.5	25.5	6	CR-DTb-G3/4	CR-DTb-NPT3/4	33.5	7
CR-DTb-M32	35	8	CR-DTb-PG16	27	6	CR-DTb-G1	CR-DTb-NPT1	36	8
CR-DTb-M40	44	8	CR-DTb-PG21	33.5	7	CR-DTb-G1 1/4	CR-DTb-NPT1 1/4	46	8
CR-DTb-M50	54	9	CR-DTb-PG29	44	8	CR-DTb-G1 1/2	CR-DTb-NPT1 1/2	54	9
CR-DTb-M63	67	10	CR-DTb-PG36	55	8	CR-DTb-G2	CR-DTb-NPT2	69	10

Email:sales@idl-cr.com
Web: www.ex-cablegland.com
www.idl-cr.com
The Company's policy is one of continuous improvement and reserves the right to change specifications at any time without prior notice

IDL&CR·昂得立®
power and productivity
for a better world

Email:sales@idl-cr.com
Web: www.ex-cablegland.com
www.idl-cr.com
The Company's policy is one of continuous improvement and reserves the right to change specifications at any time without prior notice

IDL&CR·昂得立®
power and productivity
for a better world