


Version 2018

CR-KZI 铠装电缆密封接头



产品特点

- 用于编织电缆、钢丝铠装电缆、钢带铠装电缆、船用编组电缆
- 可填充胶泥对电缆的内护套提供防爆密封
- 材质可选不锈钢或黄铜镀镍
- 密封件可选丁腈橡胶或硅胶像
- 对电缆外层提供防爆密封和防水密封的作用
- 可用于爆炸性气氛IIA IIB IIC

适用电缆

应用行业

适用环境

防爆标记

防护等级

产品认证

可选附件

格兰尺寸	螺牙规格 (公制螺纹)		适用电缆范围		H mm	L mm	SW
	AG	M 系列编号	B mm	A mm			
CRM16	M16*1.5	CR-KZI12-M16	8.0-12.0	5.0-11.0	60	15	20
CRM20	M20*1.5	CR-KZI16-M20	12.0-16.2	7.0-12.0	60	15	26
CRM20L	M20*1.5	CR-KZI21-M20	16.3-21.0	11.5-16.6	62	15	30
CRM25	M25*1.5	CR-KZI21-M25	16.3-21.0	11.5-16.6	62	15	30
CRM25L	M25*1.5	CR-KZI27-M25	21.1-27.5	12.7-19.3	70	15	40
CRM32	M32*1.5	CR-KZI27-M32	21.1-27.5	12.7-19.3	70	15	40
CRM32L	M32*1.5	CR-KZI33-M32	27.6-33.7	20.4-26.5	75	15	46
CRM40	M40*1.5	CR-KZI33-M40	27.6-33.7	20.4-26.5	75	15	46
CRM40L	M40*1.5	CR-KZI41-M40	33.8-41.0	26.6-32.5	80	16	55
CRM50	M50*1.5	CR-KZI41-M50	33.8-41.0	26.6-32.5	80	16	55
CRM50L	M50*1.5	CR-KZI53-M50	41.1-53.4	32.6-39.0	85	16	65
CRM63	M63*1.5	CR-KZI53-M63	41.1-53.4	32.6-39.0	85	16	65
CRM63L	M63*1.5	CR-KZI66-M63	53.5-66.2	39.1-49.5	90	18	80
CRM78	M78*1.5	CR-KZI79-M78	66.3-79.8	49.6-62.5	95	18	96
CRM88	M88*1.5	CR-KZI89-M88	79.8-89.0	62.6-73.0	100	18	112

格兰尺寸	螺牙规格 (英制 /美制)		适用电缆范围		H mm	L mm	SW
	G 系列编号	NPT 系列编号	B mm	A mm			
CR1/2S	CR-KZI12-G1/2	CR-KZI12-NPT1/2	8.0-12.0	5.0-11.0	60	15	20
CR1/2	CR-KZI16-G1/2	CR-KZI16-NPT1/2	12.0-16.2	7.0-12.0	60	15	26
CR3/4	CR-KZI21-G3/4	CR-KZI21-NPT3/4	16.3-21.0	11.5-16.6	62	15	30
CR1	CR-KZI27-G1	CR-KZI27-NPT1	21.1-27.5	12.7-19.3	70	15	40
CR1¼	CR-KZI33-G1¼	CR-KZI33-NPT1¼	27.6-33.7	20.4-26.5	75	15	46
CR1½	CR-KZI41-G1½	CR-KZI41-NPT1½	33.8-41.0	26.6-32.5	80	16	55
CR2	CR-KZI51-G2	CR-KZI51-NPT2	41.1-51.4	32.6-39.0	85	16	65
CR2½	CR-KZI67-G2½	CR-KZI67-NPT2½	53.5-66.2	39.1-49.5	90	18	80
CR3	CR-KZI79-G3	CR-KZI79-NPT3	66.3-79.8	49.6-62.5	95	18	96
CR3½	CR-KZI89-G3½	CR-KZI89-NPT3½	79.8-89.0	62.6-73.0	100	18	112

Email:sales@idl-cr.com
Web: www.ex-cablegland.com
www.idl-cr.com


The Company's policy is one of continuous improvement and reserves the right to change specifications at any time without prior notice

IDL&CR·昂得立®

power and productivity
for a better world

Version 2018

CR-KZII 铠装电缆密封接头



产品特点

- 用于编织电缆、钢丝铠装电缆、钢带铠装电缆、船用编组电缆
- 材质可选不锈钢或黄铜镀镍
- 密封件可选丁腈橡胶或硅胶像
- 对电缆外层提供防爆密封和防水密封的作用
- 对电缆内层提供防爆密封和防水密封的作用
- 可用于爆炸性气氛IIA IIB IIC

适用电缆

应用行业

适用环境

防爆标记

防护等级

产品认证

可选附件

格兰尺寸	螺牙规格 (公制螺纹)		适用电缆范围		H mm	L mm	SW
	AG	M 系列编号	B mm	A mm			
CRM16	M16*1.5	CR-KZII12-M16	8.0-12.0	5.0-11.0	60	15	20
CRM20	M20*1.5	CR-KZII16-M20	12.0-16.2	7.0-12.0	60	15	26
CRM25	M25*1.5	CR-KZII21-M25	16.3-21.0	11.5-16.6	62	15	30
CRM25L	M25*1.5	CR-KZII27-M25	21.1-27.5	12.7-19.3	70	15	40
CRM32	M32*1.5	CR-KZII27-M32	21.1-27.5	12.7-19.3	70	15	40
CRM32L	M32*1.5	CR-KZII33-M32	27.6-33.7	20.4-26.5	75	15	46
CRM40	M40*1.5	CR-KZII33-M40	27.6-33.7	20.4-26.5	75	15	46
CRM40L	M40*1.5	CR-KZII41-M40	33.8-41.0	26.6-32.5	80	16	55
CRM50	M50*1.5	CR-KZII41-M50	33.8-41.0	26.6-32.5	80	16	55
CRM63	M63*1.5	CR-KZII53-M63	41.1-53.4	32.6-39.0	85	16	65
CRM75	M75*1.5	CR-KZII66-M75	53.5-66.2	39.1-49.5	90	18	80
CRM78	M78*1.5	CR-KZII79-M78	66.3-79.8	55.0-62.5	95	18	96
CRM88	M88*1.5	CR-KZII89-M88	79.8-89.0	62.6-73.0	100	18	112

格兰尺寸	螺牙规格 (英制 /美制)		适用电缆范围		H mm	L mm	SW
	G 系列编号	NPT 系列编号	B mm	A mm			
CR1/2S	CR-KZII12-G1/2	CR-KZII12-NPT1/2	8.0-12.0	5.0-11.0	60	15	20
CR1/2	CR-KZII16-G1/2	CR-KZII16-NPT1/2	12.0-16.2	7.0-12.0	60	15	26
CR3/4	CR-KZII21-G3/4	CR-KZII21-NPT3/4	16.3-21.0	11.5-16.6	62	15	30
CR1	CR-KZII27-G1	CR-KZII27-NPT1	21.1-27.5	12.7-19.3	70	15	40
CR1L	CR-KZII33-G1	CR-KZII33-NPT1	27.6-33.7	20.4-26.5	75	15	46
CR1¼	CR-KZII33-G1¼	CR-KZII33-NPT1¼	27.6-33.7	20.4-26.5	75	15	46
CR1¼ L	CR-KZII41-G1¼	CR-KZII41-NPT1¼	33.8-41.0	26.6-32.5	80	16	55
CR1½	CR-KZII41-G1½	CR-KZII41-NPT1½	33.8-41.0	26.6-32.5	80	16	55
CR2	CR-KZII53-G2	CR-KZII53-NPT2	41.1-53.4	32.6-39.0	85	16	65
CR2½	CR-KZII66-G2½	CR-KZII66-NPT2½	53.5-66.2	39.1-49.5	90	18	80
CR3	CR-KZII79-G3	CR-KZII79-NPT3	66.3-79.8	55.0-62.5	95	18	96
CR3L	CR-KZII89-G3	CR-KZII89-NPT3	79.8-89.0	62.6-73.0	100	18	112

Email:sales@idl-cr.com
Web: www.ex-cablegland.com
www.idl-cr.com

The Company's policy is one of continuous improvement and reserves the right to change specifications at any time without prior notice

IDL&CR·昂得立®

power and productivity
for a better world