


Version 2018

CR-CW 电缆密封接头



产品特征

- 用于钢丝铠装电缆
- 使电缆的内外护套封闭
- 通过对铠装电缆的截断保持电缆的机械维系
- 保持电缆电力传输的延续
- 材质可选不锈钢或黄铜镀镍
- 密封件可选丁腈橡胶或硅橡胶
- 对电缆的外护套提供防水密封

适用电缆

应用行业

防护等级

产品认证

可选附件

产品结构

格兰尺寸	螺纹规格 (公制)		电缆直径		扳手径 SW	螺纹长 度 L
	AG	订货编号	A mm	B mm		
CW20	M20*1.5	CR-KZ16-CW20	12.6	16	22	10
CW20L	M20*1.5	CR-KZ21-CW20	15.9	21	27	10
CW25	M25*1.5	CR-KZ21-CW25	15.9	21	27	10
CW25L	M25*1.5	CR-KZ27-CW25	20.6	27	35	10
CW32	M32*1.5	CR-KZ27-CW32	20.6	27	35	10
CW32L	M32*1.5	CR-KZ34-CW32	26.5	34	42	10
CW40	M40*1.5	CR-KZ34-CW40	26.5	34	42	10
CW40L	M40*1.5	CR-KZ42-CW40	34.9	42.5	52	15
CW50	M50*1.5	CR-KZ50-CW50	44.6	50	65	15
CW50L	M50*1.5	CR-KZ56-CW50	44	56	65	15
CW63	M63*1.5	CR-KZ62-CW63	57	62	82	15
CW75	M75*1.5	CR-KZ68-CW75	58	68	82	15
CW75L	M75*1.5	CR-KZ79-CW75	68	79.5	96	15
CW80	M80*1.5	CR-KZ83-CW80	74	83	100	15
CW88	M88*1.5	CR-KZ91-CW88	80	91	110	15
CW100	M100*1.5	CR-KZ100-CW100	93	100	120	15

格兰尺寸	螺纹规格 (英制 /美制)		电缆直径		扳手径 SW	螺纹长 度 L
	AG	订货编号	A mm	B mm		
CW1/2	1/2"	CR-KZ16-CW1/2	12.6	16	22	10
CW1/2L	1/2"	CR-KZ21-CW1/2	15.9	21	27	10
CW3/4	3/4"	CR-KZ27-CW3/4	20.6	27	35	10
CW1	1"	CR-KZ34-CW1	26.5	34	42	10
CW1¼	1¼"	CR-KZ42-CW1¼	34.9	42.5	52	15
CW1½	1½"	CR-KZ50-CW1½	44.6	50	65	15
CW1½L	1½"	CR-KZ56-CW1½	44	56	65	15
CW2	2"	CR-KZ62-CW2	57	62	82	15
CW2½	2½"	CR-KZ68-CW2½	58	68	82	15
CW2½L	2½"	CR-KZ79-CW2½	68	79.5	96	15
CW3	3"	CR-KZ83-CW3	74	83	100	15
CW3½S	3½"	CR-KZ91-CW3½	80	91	110	15
CW3½	3½"	CR-KZ100-CW3½	93	100	120	15

Email:sales@idl-cr.com
Web: www.ex-cablegland.com
www.idl-cr.com


The Company's policy is one of continuous improvement and reserves the right to change specifications at any time without prior notice

IDL&CR·昂得立®

power and productivity
for a better world

Version 2018

CR-L 电缆密封接头



产品特征

- 适用于非铠装电缆
- 材质可选不锈钢或黄铜镀镍
- 密封件可选三元乙丙橡胶或硅橡胶
- 对电缆外层提供防水密封的作用

适用电缆

应用行业

适用环境

防爆标记

防护等级

产品认证

可选附件

公制螺纹 订货编号	适用电缆 A mm	螺纹长度 L mm	扳手径 SW
CR-L04-M8*1.25	2.0-4.2	6	11/11
CR-L06-M8*1.25	3.0-6.0	6	11/11
CR-L06-M10*1.5	3.0-6.0	6	12/14
CR-L06-M12*1.5	3.0-6.5	7	14/14
CR-L08-M12*1.5	3.5-8.0	8	14/18
CR-L08-M14*1.5	4.0-8.0	7	18/18
CR-L08-M16*1.5	3.5-8.0	8	18/18
CR-L10-M16*1.5	5.0-10.0	8	18/20
CR-L10-M18*1.5	4.5-10.0	8	20/20
CR-L10-M20*1.5	5.0-10.0	9	22/20
CR-L12-M20*1.5	6.5-12	9	22/22
CR-L14-M20*1.5	9.0-14	9	22/24
CRL14-M22*1.5	9.8-14	9	24/24
CR-L14-M24*1.5	9.8-14	10	24/24
CR-L16-M25*1.5	11.8-16	10	28/28
CR-L18-M25*1.5	13-18	10	28/30
CR-L18-M27*2	13-18	11	30/30
CR-L18-M30*2	13-18	11	32/32
CR-L20-M30*2	14-20	11	32/32
CR-L22-M32*1.5	17-22	11	36/36
CR-L22-M33*2	15-22	11	36/36
CR-L25-M36*2	18-25	12	40/40
CR-L28-M40*1.5	22-28	12.5	42/42
CR-L28-M42*2	22-28	12.5	45/42
CR-L32-M48*2	25-32	13	52/52
CR-L38-M50*1.5	28-38	13	54/54
CR-L44-M60*2	34-44	14	64/64
CR-L44-M63*1.5	34-44	14	70/70
CR-L44-M64*2	37-44	15	70/70
CR-L52-M72*2	42-52	15	85/88
CR-L55-M76*2	44-55	15	85/88
CR-L60-M80*2	55-60	15	85/88
CR-L70-M88*2	65-70	20	98/98
CR-L82-M100*2	70-82	20	101/101
CR-L90-M110*2	75-90	20	120/120
CR-L108-M125*3	95-108	20	134/134
CR-L125-M150*3	100-125	20	161/161

英制螺纹 订货编号	适用电缆 A mm	螺纹长度 L mm	扳手径 SW
CR-L06-G1/4	2.0-6.0	6	17/14
CR-L08-G3/8	3.0-8.0	7	18/18
CR-L12-G1/2	6.0-12.0	8	23/22
CR-L18-G3/4	11.0-18	11	30/30
CR-L22-G1	15-22	11	36/36
CR-L28-G1-1/4	22-28	12	48/48
CR-L38-G1-1/2	26-38	13	52/52
CR-L44-G2	37-44	14	64/64
CR-L52-G2.5	42-52	15	88/88
CR-L70-G3	65-70	20	98/98

美制螺纹 订货编号	适用电缆 A mm	螺纹长度 L mm	扳手径 SW
CR-L06-NPT1/4	2.0-6.0	6	17/14
CR-L08-NPT3/8	4.0-8.0	7	F:18
CR-L12-NPT1/2	6.0-12	8	F:22
CR-L18-NPT3/4	11.0-18	10	F:30
CR-L22-NPT1	15-22	11	F:36
CR-L28-NPT1-1/4	22-28	12	F:48
CR-L38-NPT1-1/2	26-38	13	F:52
CR-L44-NPT2	37-44	14	F:64
CR-L52-NPT2.5	42-52	15	F:88
CR-L70-NPT3	65-70	20	F:98

德制螺纹 订货编号	适用电缆 A mm	螺纹长度 L mm	扳手径 SW
CR-L06-PG7	3.0-6.2	7	14/14
CR-L08-PG9	3.5-8	8	18/18
CR-L10-PG11	4.0-10	8	20/20
CR-L12-PG13.5	6.5-12	9	23/22
CR-L14-PG16	8.5-14	9	24/24
CR-L18-PG21	10.5-18	10	30/30
CR-L25-PG29	18-25	12	40/40
CR-L32-PG36	22-32.5	13	52/52
CR-L38-PG42	26-38	13.5	58/58
CR-L44-PG48	37-44	14	64/64

Email:sales@idl-cr.com
Web: www.ex-cablegland.com
www.idl-cr.com

The Company's policy is one of continuous improvement and reserves the right to change specifications at any time without prior notice

IDL&CR·昂得立®

power and productivity
for a better world