


Version 2018
CR-F 电缆密封接头



产品特点

- 适用于非铠装电缆
- 材质可选不锈钢或黄铜镀镍
- 密封件可选三元乙丙橡胶或硅胶像
- 对电缆外层提供防爆密封和防水密封的作用
- 可用于爆炸性氛围IIA IIB IIC

适用电缆

应用行业

适用环境

防爆标记

防护等级

产品认证

可选附件

格兰尺寸	螺牙规格 (美制螺纹)		螺牙规格 (英制螺纹)		A mm	L mm	SW
	AG	订货号	AG	订货号			
CR1/2	NPT1/4	CR-F06-NPT1/4	G1/4	CR-F06-G1/4	3.0-6.0	8	14
CR3/8	NPT3/8	CR-F08-NPT3/8	G3/8	CR-F08-G3/8	4.5-8.0	9	18
CR3/8L	NPT3/8	CR-F10-NPT3/8	G3/8	CR-F10-G3/8	6.0-10	9	22
CR1/2	NPT1/2	CR-F12-NPT1/2	G1/2	CR-F12-G1/2	6.5-11	9.5	24
CR1/2L	NPT1/2	CR-F14-NPT1/2	G1/2	CR-F14-G1/2	9.0-14	9.5	26
CR3/4S	NPT3/4	CR-F16-NPT3/4	G3/4	CR-F16-G3/4	12-16	12	28/30
CR3/4	NPT3/4	CR-F18-NPT3/4	G3/4	CR-F18-G3/4	13-18	12	32
CR1S	NPT1	CR-F22-NPT1	G1	CR-F22-G1	16-23	12.5	38
CR1	NPT1	CR-F25-NPT1	G1	CR-F25-G1	18-25	12.5	40
CR1¼	NPT1¼	CR-F32-G1¼	G1¼	CR-F32-G1¼	26-32	15	50
CR1½	NPT1½	CR-F38-G1½	G1½	CR-F38-G1½	31-38	15	58
CR2	NPT2	CR-F46-NPT2	G2	CR-F46-G2	38-46	15	72
CR2½	NPT2½	CR-F52-NPT2½	G2½	CR-F52-G2½	42-52	15	85
CR3	NPT3	CR-F70-NPT3	G3	CR-F70-G3	65-70	15	100
CR4	NPT4	CR-F102-NPT4	G4	CR-F102-G4	90-102	18	126

格兰尺寸	螺牙规格 (公制螺纹)		适用电缆	螺纹长度	扳手直径
	AG	订货号			
CRM6	M6*1	CR-F03-M6	2.0-3.0	5	10
CRM8	M8*1	CR-F04-M8	2.0-4.0	6	12
CRM10	M10*1.5	CR-F06-M10	3.0-6.0	6	14
CRM12S	M12*1.5	CR-F06-M12	3.0-6.0	8	14
CRM12	M12*1.5	CR-F08-M12	4.5-8.0	8	18
CRM16	M16*1.5	CR-F08-M16	4.5-8.0	9	18
CRM16L	M16*1.5	CR-F10-M16	6.0-10	9	22
CRM18	M18*1.5	CR-F10-M18	6.0-10	9	22
CRM20	M20*1.5	CR-F12-M20	6.5-11.5	9.5	24
CRM20L	M20*1.5	CR-F14-M20	9.0-14	9.5	26
CRM22	M22*1.5	CR-F14-M22	9.0-14	9.5	26
CRM24	M24*1.5	CR-F14-M24	9.0-14	12	26
CRM25S	M25*1.5	CR-F16-M25	12-16	12	28/30
CRM25	M25*1.5	CR-F18-M25	13-18	12	32
CRM27	M27*2	CR-F18-M27	13-18	12	32
CRM30S	M30*2	CR-F18-M30	13-18	12.5	32/34
CRM30	M30*2	CR-F23-M30	16-23	12.5	38
CRM32S	M32*1.5	CR-F23-M32	16-23	12.5	38
CRM32	M32*1.5	CR-F25-M32	18-25	12.5	40
CRM36	M36*2	CR-F25-M36	18-25	12.5	40
CRM40S	M40*1.5	CR-F30-M40	24-30	15	48/50
CRM40	M40*1.5	CR-F32-M40	26-32	15	50
CRM42	M42*2	CR-F32-M42	26-32	15	50
CRM48	M48*2	CR-F32-M48	26-32	15	56
CRM50	M50*1.5	CR-F38-M50	31-38	15	58
CRM50L	M50*1.5	CR-F41-M50	36-41	15	60
CRM63	M63*1.5	CR-F46-M63	38-46	15	72
CRM63L	M63*1.5	CR-F52-M63	42-52	15	75
CRM75	M75*1.5	CR-F52-M75	42-52	15	85
CRM75L	M75*1.5	CR-F60-M75	55-60	15	85
CRM78	M78*2	CR-F60-M78	55-60	15	85
CRM78L	M78*2	CR-F66-M78	60-66	15	85
CRM88	M88*2	CR-F70-M88	65-70	15	100
CRM88L	M88*2	CR-F77-M88	67-77	18	104
CRM100	M100*2	CR-F85-M100	75-85	18	116
CRM100L	M100*2	CR-F90-M100	80-90	18	116
CRM110	M110*2	CR-F102-M110	90-102	18	126
CRM120	M120*2	CR-F112-M120	102-112	18	138
CRM130	M130*2	CR-F125-M130	112-125	18	142

格兰尺寸	螺牙规格 (德制螺纹)		适用电缆	螺纹长度	扳手直径
	AG	订货号			
CR12	PG7	CR-F06-PG7	3.0-6.0	8	14
CR16	PG9	CR-F08-PG9	4.5-8.0	9	18
CR18	PG11	CR-F10-PG11	6.0-10	9	22
CR20	PG13.5	CR-F12-PG13.5	6.5-11	9.5	24
CR22	PG16	CR-F14-PG16	9.0-14	9.5	26
CR25	PG21	CR-F18-PG21	12-16	12	28/30
CR32	PG29	CR-F25-PG29	18-25	12.5	40
CR40	PG36	CR-F32-PG36	24-32	15	48/50
CR50	PG42	CR-F38-PG42	31-38	15	58
CR63	PG48	CR-F46-PG48	38-46	15	72
CR75	PG63	CR-F52-PG63	42-52	15	85

Email:sales@idl-cr.com
Web: www.ex-cablegland.com
www.idl-cr.com
The Company's policy is one of continuous improvement and reserves the right to change specifications at any time without prior notice

IDL&CR·昂得立®
power and productivity
for a better word

Email:sales@idl-cr.com
Web: www.ex-cablegland.com
www.idl-cr.com
The Company's policy is one of continuous improvement and reserves the right to change specifications at any time without prior notice

IDL&CR·昂得立®
power and productivity
for a better word