


Version 2018

CR-KZ 铠装电缆密封接头



产品特点

- 用于编织电缆或钢带铠装电缆
- 材质可选不锈钢或黄铜镀镍
- 密封件可选三元乙丙橡胶或硅胶
- 对电缆外层提供防爆密封和防水密封的作用
- 可用于爆炸性气氛IIA IIB IIC

适用电缆

应用行业

适用环境

防爆标记

防护等级

产品认证

可选附件

| 格兰尺寸 | 型号规格 (公制螺纹) | | 适用电范围 | | | | |
|--------|-------------|---------------|----------|-------|------|------|-----|
| | AG | M系列编号 | B mm | A mm | H mm | L mm | SW |
| CRM16S | M16*1.5 | CR-KZ08-M16 | 5-8 | 3-6 | 30 | 12 | 24 |
| CRM16 | M16*1.5 | CR-KZ10-M16 | 6-10 | 4-8 | 30 | 12 | 24 |
| CRM20S | M20*1.5 | CR-KZ14-M20 | 9-14 | 6-11 | 30 | 12 | 24 |
| CRM20L | M20*1.5 | CR-KZ16-M20 | 10-16 | 7-12 | 30 | 12 | 24 |
| CRM25S | M25*1.5 | CR-KZ18-M25 | 13-18 | 9-14 | 32 | 12 | 30 |
| CRM25 | M25*1.5 | CR-KZ21-M25 | 15-21 | 11-17 | 35 | 13 | 36 |
| CRM25L | M25*1.5 | CR-KZ24-M25 | 17-24 | 13-20 | 35 | 13 | 40 |
| CRM32 | M32*1.5 | CR-KZ28-M32 | 20-28 | 16-23 | 39 | 15 | 46 |
| CRM32L | M32*1.5 | CR-KZ32-M32 | 23-32 | 18-26 | 39 | 15 | 46 |
| CRM40 | M40*1.5 | CR-KZ35-M40 | 26-35 | 21-29 | 43 | 15 | 55 |
| CRM40L | M40*1.5 | CR-KZ38-M40 | 31-38 | 25-32 | 43 | 15 | 55 |
| CRM50 | M50*1.5 | CR-KZ41-M50 | 34-41 | 28-35 | 48 | 15 | 65 |
| CRM50L | M50*1.5 | CR-KZ44-M50 | 37-44 | 31-38 | 48 | 15 | 65 |
| CRM63 | M63*1.5 | CR-KZ50-M63 | 40-50 | 33-43 | 53 | 16 | 80 |
| CRM63L | M63*1.5 | CR-KZ55-M63 | 43-55 | 36-47 | 53 | 16 | 80 |
| CRM75 | M75*1.5 | CR-KZ63-M75 | 50-63 | 42-53 | 58 | 16 | 96 |
| CRM75L | M75*1.5 | CR-KZ68-M75 | 54-68 | 45-58 | 58 | 16 | 96 |
| CRM88 | M88*2 | CR-KZ72-M88 | 62-72 | 52-62 | 64 | 18 | 114 |
| CRM88L | M88*2 | CR-KZ79-M88 | 67-79 | 56-67 | 64 | 18 | 114 |
| CRM100 | M100*2 | CR-KZ89-M100 | 78-89 | 65-75 | 70 | 18 | 128 |
| CRM110 | M110*2 | CR-KZ105-M110 | 88-104.5 | 74-91 | 70 | 18 | 138 |

| 格兰尺寸 | 型号规格 (公制螺纹) | | 适用电范围 | | H mm | L mm | SW |
|--------|-------------|----------------|-------|-------|------|------|----|
| | AG | M系列编号 | B mm | A mm | | | |
| CRM20S | PG13.5 | CR-KZ14-PG13.5 | 9-14 | 6-11 | 30 | 12 | 24 |
| CRM20L | PG16 | CR-KZ16-PG16 | 10-16 | 7-12 | 30 | 12 | 24 |
| CRM25 | PG21 | CR-KZ21-PG21 | 15-21 | 11-17 | 35 | 13 | 36 |
| CRM32 | PG25 | CR-KZ28-PG25 | 20-28 | 16-23 | 39 | 15 | 46 |
| CRM32L | PG29 | CR-KZ32-PG29 | 23-32 | 18-26 | 39 | 15 | 46 |
| CRM40 | PG36 | CR-KZ35-PG36 | 26-35 | 21-29 | 43 | 15 | 55 |
| CRM50 | PG42 | CR-KZ41-PG42 | 34-41 | 28-35 | 48 | 15 | 65 |
| CRM63 | PG48 | CR-KZ50-PG48 | 40-50 | 33-43 | 53 | 16 | 80 |
| CRM75 | PG63 | CR-KZ63-PG63 | 50-63 | 42-53 | 58 | 16 | 96 |

| 格兰尺寸 | 型号规格 (英制 / 美制) | | 适用电范围 | | H mm | L mm | SW |
|----------|------------------|----------------|----------|-------|------|------|-----|
| | NPT系列编号 | G系列编号 | B mm | A mm | | | |
| CR3/8 | CR-KZ08-NPT3/8 | CR-KZ08-G3/8 | 5-8 | 3-6 | 30 | 12 | 24 |
| CR1/2S | CR-KZ10-NPT1/2 | CR-KZ10-G1/2 | 6-10 | 4-8 | 30 | 12 | 24 |
| CR1/2 | CR-KZ14-NPT1/2 | CR-KZ14-G1/2 | 9-14 | 6-11 | 30 | 12 | 24 |
| CR1/2L | CR-KZ16-NPT1/2 | CR-KZ16-G1/2 | 10-16 | 7-12 | 30 | 12 | 24 |
| CR3/4S | CR-KZ18-NPT3/4 | CR-KZ18-G3/4 | 13-18 | 9-14 | 32 | 12 | 30 |
| CR3/4 | CR-KZ21-NPT3/4 | CR-KZ21-G3/4 | 15-21 | 11-17 | 35 | 13 | 36 |
| CR3/4L | CR-KZ24-NPT3/4 | CR-KZ24-G3/4 | 17-24 | 13-20 | 35 | 13 | 40 |
| CR1S | CR-KZ28-NPT1 | CR-KZ28-G1 | 20-28 | 16-23 | 39 | 15 | 46 |
| CR1 | CR-KZ32-NPT1 | CR-KZ32-G1 | 23-32 | 18-26 | 39 | 15 | 46 |
| CR1 1/4 | CR-KZ35-NPT1 1/4 | CR-KZ35-G1 1/4 | 26-35 | 21-29 | 43 | 15 | 55 |
| CR1 1/4L | CR-KZ38-NPT1 1/4 | CR-KZ38-G1 1/4 | 31-38 | 25-32 | 43 | 15 | 55 |
| CR1 1/2 | CR-KZ41-NPT1 1/2 | CR-KZ41-G1 1/2 | 34-41 | 28-35 | 48 | 15 | 65 |
| CR1 1/2L | CR-KZ44-NPT1 1/2 | CR-KZ44-G1 1/2 | 37-44 | 31-38 | 48 | 15 | 65 |
| CR2 | CR-KZ50-NPT2 | CR-KZ50-G2 | 40-50 | 33-43 | 53 | 16 | 80 |
| CR2L | CR-KZ55-NPT2 | CR-KZ55-G2 | 43-55 | 36-47 | 53 | 16 | 80 |
| CR2 1/2 | CR-KZ63-NPT2 1/2 | CR-KZ63-G2 1/2 | 50-63 | 42-53 | 58 | 16 | 96 |
| CR2 1/2L | CR-KZ68-NPT2 1/2 | CR-KZ68-G2 1/2 | 54-68 | 45-58 | 58 | 16 | 96 |
| CR3 | CR-KZ72-NPT3 | CR-KZ72-G3 | 62-72 | 52-62 | 64 | 18 | 114 |
| CR3L | CR-KZ79-NPT3 | CR-KZ79-G3 | 67-79 | 56-67 | 64 | 18 | 114 |
| CR3 1/2 | CR-KZ89-NPT3 1/2 | CR-KZ89-G3 1/2 | 78-89 | 65-75 | 70 | 18 | 128 |
| CR4 | CR-KZ105-NPT4 | CR-KZ105-G4 | 88-104.5 | 74-91 | 70 | 18 | 138 |

Email:sales@idl-cr.com
Web: www.ex-cablegland.com
www.idl-cr.com

The Company's policy is one of continuous improvement and reserves the right to change specifications at any time without prior notice

IDL&CR·昂得立®

power and productivity
for a better word

Email:sales@idl-cr.com
Web: www.ex-cablegland.com
www.idl-cr.com

The Company's policy is one of continuous improvement and reserves the right to change specifications at any time without prior notice

IDL&CR·昂得立®

power and productivity
for a better word